

Solid State Broadband High Power Amplifier

2211
2700 - 3200 MHz / 1200 Watts Pulse

The Model 2211 is suitable for band specific high power pulse applications. This amplifier utilizes high power GaN SiC devices that provide wide frequency response, high gain, high peak power capability, and low distortions. Exceptional performance, long-term reliability and high efficiency are achieved by employing advanced broadband RF matching networks and combining techniques, EMI/RFI filters, and all qualified components. The amplifier is constructed within single 3RU drawer including the forced air-cooling. Available operating voltage configuration are single phase 100-260 VAC up to 400 hertz and 28 VDC.



SKU#: 2211-001

The amplifier includes a built in control and monitoring system, with protection functions which preserve high availability. Remote management and diagnostics are via an embedded web server allowing network managed site status and control simply by connecting the unit's Ethernet port to a LAN. Using a web browser and the unit's IP address (IPV4) allows ease of access with the benefit of multi-level security. The control system core runs an embedded OS (Linux), has a built-in non-volatile memory for event recording, and factory setup recovery features. The extended memory option allows storage of control parameters and event logs.

Empower RF's ISO9001:2015 Quality Assurance Program assures consistent performance and the highest reliability.

- Solid-state Class AB, compact modular design
- Suitable for Pulse applications
- Embedded directional coupler – Eliminates the need for external component
- 50 ohm input/output impedance
- Built-in Control, Monitoring and Protection functions
- High reliability and ruggedness

ELECTRICAL SPECIFICATIONS over temperature conditions (-10 to +40°C)

Parameter	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	2700		3200	MHz
Output Power @ Pulse condition Duty Cycle = 2% Pulse Width = 1-10 μSec	P _{SAT-PK}	1200			Watt
Pulse Droop	P _{DROOP}			0.5	dB
Pulse Rise/Fall Time	T _{RISE}			250	nSec
	T _{FALL}			150	
Power Gain @ 1dB Gain Compression	G _{1dB}	62			dB
Input Power for Rated P _{SAT}	P _{IN}		0		dBm
Input Power Range	P _{IN}	-5.0		+5.0	dBm
Small Signal Gain Flatness / Leveled ALC	ΔG			±1.5/±0.75	dB
Gain Adjustment Range	VVA	20			dB
Input Return Loss	S ₁₁			-10	dB
Noise Figure @ maximum gain	NF			20	dB
Harmonics @ P _{OUT} = 1200W _{PK}	2 ND /3 RD				dBc
Spurious Signals	Spur			-60	dBc
Operating Voltage – 1-phase	V _{AC}	100		260	Volt
Power Consumption @ 1200W _{PK} @ 2%DC	P _D			500	VA
Switching Speed	T _{ON/OFF}			1	μSec

MECHANICAL SPECIFICATIONS

Parameter	Value	Unit
Dimensions W x H x D (exclude connectors, handles and brackets)	17 x 5.25 x 22	Inch
Weight	68	Pound
RF Connectors Input/Output	Input: Type-N, Female Output: Type-N, Female, (Optional: Type-SC, Female)	RF IN RF OUT
RF Sample Connectors	Type-SMA, Female	Forward /Reverse
Blanking/Gating Input Connector	Type-BNC, Female	Blanking
Cooling	Built-in forced air cooling system – front to rear	Airflow Direction

Solid State Broadband High Power Amplifier

2211
2700 - 3200 MHz / 1200 Watts Pulse
ENVIRONMENTAL CHARACTERISTICS (Qualification Data available for review)

Parameter	Symbol	Min	Typ	Max	Unit
Operating Ambient Temperature	T _A	-10		+40	°C
Non-operating Temperature	T _{STG}	-40		+85	°C
Relative Humidity (non-condensing)	RH			95	%
Shock / Vibration - MIL-STD-810F Shock Method 516.5, Vibration Method 514.5	SH / VI				

PROTECTIONS

Parameter	Specification	Unit
Input Overdrive	+10 dBm	Max
VSWR protection	At 3:1 – PA backs-off output power to a safe operating level – no system shutdown, “On Air” time is maximized	-
Thermal – Graceful Degradation	Ambient 40°C	Min
Default Data Recovery	Factory Default Calibration Recovery	

COMMUNICATION INTERFACES


Function	Utility	Connector
Ethernet	Network management of device / web interface	RJ45
USB	Mass storage / Expansion Bus	USB 1.x/2.0 compatible
RS-232 standard (RS-422 – factory configurable)	Serial management of device / local operator access	D-Sub 9-position Male

SYSTEM I/O CONNECTOR – 14-Position

Pin #	Description	Specification
1	FWD Test Point	Forward detected power (analog voltage: 0-5 Volt)
2	REV Test Point	Reverse detected power (analog voltage: 0-5 Volt)
3	Summary Fault	Summary Fault: Active TTL Logic Low ($\leq 0.7V$) (Internally Pulled-High)
4	N/A	No Connection
5	Shutdown	Amplifier Disable: TTL Logic Low ($\leq 0.7V$) (Internally Pulled-High)
6	Aux P/S Test Point	+12.0V _{DC} $\pm 2.0V$ (resettable 0.5amp fuse)
7	Main P/S Test Point	+44.0V _{DC} $\pm 4.8V$ (resettable 0.5amp fuse)
8	GND	Ground
9-11	Open drain control	Site management utility (reserved)
12&13	Digital I/O (configurable)	Site management utility (reserved)
14	GND	Ground

Available Options

2211-00X
-001 100-240 VAC, 1-phase, 47-63 Hz, Rear RF Connectors
-002 TBD
-003 TBD
-004 TBD
Contact us for other available options; sales@empowerrf.com
Standard Feature:
-LCD Control, Ethernet & Serial Comm
-Main RF Connectors: Input & Output [Type-N, F] (standard)
-Sample Port: SMA-F [Forward & Reverse]
-Blanking/Gating Port: BNC-F
-Rack Slides, Handles and Rackmount Bracket

NOTIONAL BLOCK DIAGRAM


Solid State Broadband High Power Amplifier

2211

2700 - 3200 MHz / 1200 Watts Pulse

MECHANICAL OUTLINE (with Rear RF connectors)

