

Solid State High Power Amplifier

2232
5200 – 5900 MHz / 2.5 kW_{PK} Pulsed

The 2232 is a single drawer unit that produces a minimum output of 2.5 kW peak pulsed power and 500W CW power. The amplifier features multiple high power GaN on SiC devices that provide wide frequency response, high gain, high peak power capability, and low distortions. Exceptional performance, long-term reliability and high efficiency are achieved by employing advanced broadband RF matching networks and combining techniques, EMI/RFI filters, and all qualified components. The amplifier includes integral forced air-cooling fans. Available operating voltage configurations are single phase, three phase AC up to 400 hertz and 28 volts DC



The amplifier includes a built-in control and monitoring system, with protection functions which preserve maximum output capability and reliability. Remote management and diagnostics are via an embedded web server allowing network managed site status and control simply by connecting the unit's Ethernet port to a LAN. Using a web browser and the unit's IP address (IPV4) allows ease of access with the benefit of multilevel security. The control system core supports hardware encryption, runs an embedded OS (Linux), has a built-in non-volatile memory for event recording, and factory setup recovery features. The extended memory option allows storage of control parameters and event logs.

We are delivering more than just RF power, the next generation family of systems provide dynamic adjustments linked to the processing power and digital controls, which focus on maximizing system availability time as well as power output under ALL conditions.

Empower RF's ISO9001:2015 Quality Assurance Program assures consistent performance and the highest reliability.

- Solid-state class AB design
- Suitable for instantaneous pulse operation over the operating band.
- Compact Modular design and scalable architecture
- 50 ohm input/output impedance
- Built-in Control, Monitoring and Protection functions
- High reliability and ruggedness

ELECTRICAL SPECIFICATIONS over temperature conditions (0 to +50°C)

| Parameter | Symbol | Min | Typical | Max | Unit |
|---|----------------------------------|------|---------|---------|---------|
| Operating Frequency | BW | 5200 | | 5900 | MHz |
| Power Output – Peak Pulse | P _{SAT_PK} | 2500 | | | Watt |
| Power Output – CW | P _{SAT_CW} | 500 | | | Watt |
| Pulse Width @ Duty Cycle 20%(NOTE) | P _{WIDTH} | 1 | | 500 | µSec |
| Duty Cycle | | 0.5 | | 20 | % |
| Pulse Repetition Rate Frequency | PRF | 0.5 | | 25 | kHz |
| Power Gain @ Rated Peak P _{OUT} - Pulse | G _{PK} | 65 | | | dB |
| Pulse Droop @ 500µSec Pulse Width | P _{DRPOOP} | | 1.2 | 1.5 | dB |
| Modulated Pulse Rise/Fall Time (10% to 90%) | T _{RISE/T_FALL} | | 70/70 | 150/150 | nSec |
| Input power for rated Output – Pulse & CW signal | P _{IN} | | -5 | 0 | dBm |
| Input Return Loss | S ₁₁ | | | -10 | dB |
| NPO – Noise Power Output | Enabled | | | -10 | dBm/MHz |
| | Disabled | | | -106 | |
| Harmonics @ P _{OUT_PULSE} = 2.5kW _{PK} | 2 ND -5 TH | | -40 | | dBc |
| Spurious Signals | Spur | | | -60 | dBc |
| Operating Voltage | 3-phase (Line-to-Line) | | | 260 | Volt |
| | 1-Phase | | | 260 | |
| Power Consumption @ 20% _{DC} , P _{OUT_PULSE} = 2.5W _{PK} | P _D | | 1350 | 1750 | VA |

NOTE: Call factory for application >20% duty cycle.

PROTECTIONS

| Parameter | Specification | Unit |
|-----------------------|---|------|
| Input Overdrive | ≥10 dBm – Shutdown | - |
| Load VSWR Protection | The unit disables the RF when reverse power exceeds the safe level @ all load phase & amplitude | - |
| Thermal Shutdown | Baseplate ≥90 °C | - |
| Default Data Recovery | Factory Default Calibration Recovery | - |

Solid State High Power Amplifier

2232
5200 – 5900 MHz / 2.5 kW_{PK} Pulsed

MECHANICAL SPECIFICATIONS

| Parameter | Value | Unit |
|--|---|-------------------|
| Overall Dimension (W x H x D) (excludes handles, connectors and brackets) | 17.5 x 8.75 x 22.0 | Inch |
| Total Weight | 95 | Pound |
| RF Connectors Input/Output | Input: N-Type, Female Output: 7/16-DIN, Female | RF IN RF OUT |
| RF Sample Connectors | Type-SMA, Female | Forward / Reverse |
| Blanking/Gating Input Connector | BNC Female | Blanking |
| Cooling | Built-in forced-air system – Front-to-Rear | Airflow Direction |

ENVIRONMENTAL CHARACTERISTICS:

| Parameter | Symbol | Min | Typ | Max | Unit |
|---|------------------|-----|-----|--------|------|
| Operating Ambient Temperature <i>NOTE 1</i> | T _C | -10 | | +50 | °C |
| Non-operating Temperature | T _{STG} | -35 | | +75 | °C |
| Relative humidity (non-condensing) | RH | | | 95 | % |
| Altitude (MIL-STD-810F) | ALT | | | 10,000 | Feet |
| Shock / Vibration (MIL-STD-810F, Shock Method 516.5, Vibration Method 514.5) | SH / VI | | | | - |

Note: 1. Call factory for extended operating temperature range.

COMMUNICATION INTERFACES:

| Function | Utility | Connector |
|--|--|------------------------|
| Ethernet | Network management of device / web interface | RJ45 |
| USB | Mass Storage / Expansion Bus | USB 1.x/2.0 compatible |
| RS-232, Standard (RS-422, factory configurable) | Serial management device / local operator access | D-sub, 9-position Male |

SYSTEM I/O CONNECTOR – 14-Position

| Pin # | Description | Specification |
|-------|----------------------------|---|
| 1 | FWD Test Point | Forward detected power (analog voltage: 0-5 Volt) |
| 2 | REV Test Point | Reverse detected power (analog voltage: 0-5 Volt) |
| 3 | Summary Fault | Summary Fault: Active TTL Logic Low ($\leq 0.7V$) (Internally Pulled-High) |
| 4 | N/C | No Connection (reserved) |
| 5 | Shutdown | Amplifier Disable: TTL Logic Low ($\leq 0.7V$) (Internally Pulled-High) |
| 6 | Aux P/S Test Point | +12.0V _{DC} $\pm 2.0V$ (resettable 0.5amp fuse) |
| 7 | Main P/S Test Point | +44.0V _{DC} $\pm 4.8V$ (resettable 0.5amp fuse) |
| 8 | GND | Ground |
| 9-11 | Open drain control | Site management utility (reserved) |
| 12&13 | Digital I/O (configurable) | Site management utility (reserved) |
| 14 | GND | Ground |

Available Options

2232-00X

-001 180-260 VAC, 3-phase-Delta, 47-63 Hz, Rear RF Connectors


-002 TBD

Contact us for other available options; sales@empowerrf.com

Standard Feature:

- LCD Control, Ethernet & Serial Comm
- Sample Port: SMA-F [Forward & Reverse]
- Blanking/Gating Port: BNC-F
- Rack Slides, Handles and Rackmount Brackets

NOTIONAL BLOCK DIAGRAM



Solid State High Power Amplifier

2232

5200 – 5900 MHz / 2.5 kW_{PK} Pulsed

OUTLINE

