

Solid State Broadband High Power Amplifier

2211
2700 - 3100 MHz / 1200 Watts Pulse

The Model 2211 is suitable for band specific high power pulse applications. This amplifier utilizes high power GaN devices that provide wide frequency response, high gain, high peak power capability, and low distortions. Exceptional performance, long-term reliability and high efficiency are achieved by employing advanced broadband RF matching networks and combining techniques, EMI/RFI filters, and all qualified components. The amplifier is constructed within single 3RU drawer including the forced air-cooling. Available operating voltage configuration are single phase 100-260 VAC up to 400HZ and 28 VDC.



SKU#: 2211-001

The amplifier includes a built in control and monitoring system, with protection functions which preserve high availability. Remote management and diagnostics are via an embedded web server allowing network managed site status and control simply by connecting the unit's Ethernet port to a LAN. Using a web browser and the unit's IP address (IPV4) allows ease of access with the benefit of multi-level security. The control system core runs an embedded OS (Linux), has a built-in non-volatile memory for event recording, and factory setup recovery features. The extended memory option allows storage of control parameters and event logs.

Empower RF's ISO9001 Quality Assurance Program assures consistent performance and the highest reliability.

- Solid-state Class AB, compact modular design
- Suitable for CW, AM, FM, Pulse and some linear applications (Consult factory for other modulation types)
- Embedded directional coupler – Eliminates the need for external component
- 50 ohm input/output impedance
- Built-in Control, Monitoring and Protection functions
- High reliability and ruggedness

Preliminary

ELECTRICAL SPECIFICATIONS over temperature conditions (-10 to +40°C)

Parameter	Symbol	Min	Typ	Max	Unit
Operating Frequency	BW	2700		3100	MHz
Output Power @ Pulse condition Duty Cycle = 2% Pulse Width = 1-10 μ Sec	P_{SAT-PK}	1200			Watt
Pulse Droop	P_{DROOP}			0.5	dB
Pulse Rise/Fall Time	T_{RISE}			250	nSec
	T_{FALL}			150	
Power Gain @ 1dB Gain Compression	G_{1dB}	62			dB
Input Power for Rated P_{SAT}	P_{IN}		0		dBm
Input Power Range	P_{IN}	-5.0		+5.0	dBm
Small Signal Gain Flatness / Leveled ALC	ΔG			$\pm 1.5/\pm 0.75$	dB
Gain Adjustment Range	VVA	20			dB
Input Return Loss	S_{11}			-10	dB
Noise Figure @ maximum gain	NF			20	dB
Harmonics @ $P_{OUT} = 1200W_{PK}$	$2^{ND}/3^{RD}$				dBc
Spurious Signals	Spur			-60	dBc
Operating Voltage – 1-phase	V_{AC}	100		260	Volt
Power Consumption @ $1200W_{PK}$ @ 2%DC	P_D			500	VA
Switching Speed	$T_{ON/OFF}$			1	μ Sec

MECHANICAL SPECIFICATIONS

Parameter	Value	Unit
Dimensions W x H x D	17.5 x 5.25 x 22	Inch
Weight	68	Pound
RF Connectors Input/Output	Type-N, Female (Optional Output: Type-SC, Female)	
RF Sample	Type-SMA, Female	
Blanking Input	Type-BNC, Female	
Cooling	Built-in forced air cooling system	

Solid State Broadband High Power Amplifier

2211

2700 - 3100 MHz / 1200 Watts Pulse

ENVIRONMENTAL CHARACTERISTICS (Qualification Data available for review)

Parameter	Symbol	Min	Typ	Max	Unit
Operating Ambient Temperature	T _A	-10		+40	°C
Non-operating Temperature	T _{STG}	-40		+85	°C
Relative Humidity (non-condensing)	RH			95	%
Shock / Vibration - MIL-STD-810F Shock Method 516.5, Vibration Method 514.5	SH / VI				

PROTECTIONS

Parameter	Specification	Unit
Input Overdrive	+10 dBm	Max
VSWR protection	At 3:1 – PA backs-off output power to a safe operating level – no system shutdown, "On Air" time is maximized	-
Thermal – Graceful Degradation	Ambient 40°C	Min
Default Data Recovery	Factory Default Calibration Recovery	

COMMUNICATION INTERFACES

Function	Utility	Connector
Ethernet	Network management of device / web interface	RJ45
USB	Mass storage / Expansion Bus	USB 1.x/2.0 compatible
RS-232, RS-422 (optional)	Serial management of device / local operator access	D-Sub 9-position Male

SYSTEM I/O CONNECTOR – 14-Position

Pin #	Description	Specification
1	FWD Test Point	Forward detected power (analog voltage: 0-5 Volt)
2	REV Test Point	Reverse detected power (analog voltage: 0-5 Volt)
3	Summary Fault	Summary Fault: Active TTL Logic Low ($\leq 0.7V$) (Internally Pulled-High)
4	N/A	No Connection
5	Shutdown	Amplifier Disable: TTL Logic Low ($\leq 0.7V$) (Internally Pulled-High)
6	Aux P/S Test Point	+12.0V _{DC} $\pm 2.0V$ (resettable 0.5amp fuse)
7	Main P/S Test Point	+44.0V _{DC} $\pm 4.8V$ (resettable 0.5amp fuse)
8	GND	Ground
9-11	Open drain control	Site management utility (reserved)
12&13	Digital I/O (configurable)	Site management utility (reserved)
14	GND	Ground

Available Options

2211-001

-001 100-240 VAC, 1-phase, 47-63 Hz, Rear RF Connectors

-002 TBD

-003 TBD

-004 TBD

 Contact us for other available options; sales@empowerrf.com

Standard Feature:

-LCD Control, Ethernet & Serial Comm


 -Main RF Connectors: **Input & Output** [Type-N, F]

-Sample Port: SMA-F [Forward & Reverse]

-Blanking/Gating Port: BNC-F

-Rack Slides, Handles and Rackmount Bracket

NOTIONAL BLOCK DIAGRAM



Solid State Broadband High Power Amplifier

2211

2700 - 3100 MHz / 1200 Watts Pulse

OUTLINE DRAWING

