

FOR IMMEDIATE RELEASE

Unprecedented X-Band Pulse Widths



Model 2221

The Empower RF 2221 amplifier operates in the 9-10 GHz X-band, delivering an impressive 8000W peak output power with long and short pulse widths. Its applications encompass radar systems, electronic warfare, HPM research, and electromagnetics effects testing. With a rugged, modular design, the 2221 offers a reliable, high-performance solution for applications demanding significant X-band power.

Key Features and Specifications

The model 2221 amplifier operates in the 9-10 GHz X-band frequency range, delivering an impressive 8 kW of peak pulsed output power. This high-performance system boasts:

- Exceptional Gain: Typical gain of 70 dB with ± 1 -dB gain flatness¹
- Versatile Pulse Capabilities: Supports 0.2 to 500- μ s pulse widths at duty cycles from 0.5 to 20.0%
- High Pulse Repetition Frequency: Operates at PRFs up to 50 kHz
- Advanced GaN Technology: Utilizes multiple GaN-on-SiC SSPAs for superior performance

Key Design Elements Include

- Compact Form Factor: Rackmount system measuring 17.50 × 26.25 × 27.05 inches
- Integrated Control: Built-in control, monitoring, and protection functions
- Efficient Cooling: Forced-air cooling system for optimal performance
- Flexible Power Supply: Operates from three-phase 180 to 260 VAC power supplies

To learn how the 2221 amplifier fits your application, contact Empower RF today and speak with one of our experts.



Empower RF Systems, Inc. Press Materials
Distribution: Unlimited
Author Date: October 9, 2024

FOR IMMEDIATE RELEASE

Learn More About This Product:

https://www.empowerrf.com/products/display_amplifier.php?sku=2221

Download datasheet:

https://www.empowerrf.com/datasheet/Empower_RF_Amplifier_2221.pdf

Complete Empower RF Amplifiers lineup:

http://www.empowerrf.com/products/rf_power_amplifier.php

Empower RF Systems is the technology leader in high power amplifier solutions for reliable communications, defense, and industrial applications. Our products incorporate the latest semiconductor and power combining technologies and originate from an extensive library of “building block” designs. Solutions range from basic modules to multifunction PA assemblies with embedded real time microprocessor control.

CONTACT

Corporate Offices:

sales@empowerrf.com

<http://www.EmpowerRF.com>

Empower RF Systems, Inc.

316 W. Florence Avenue

Inglewood, CA 90301

P: +1 (310) 412-8100

MEDIA Contact

Tatyana Safronova

Web & Print Media Manager

tatyana.safronova@empowerrf.com

Cell: 310-801-2283